





APPENDIX C

成形（不对应编带） Forming (Not Available Taping)

成形形状 Forming Style	成形型号 Forming Type Name	成形尺寸 Forming Dimension (mm)				重量 Weight g/100pcs	基本单位 Basic Unit (pcs)	直形导线型号 Straight Type Name
		P±1	H3±1orH5	H4±1orH6	d			
 L Forming	CW1/2CL10A (CW1SCL10A)	10.0	5.3	4.5±0.5	0.6	24	2000	CW1/2 (CW1S)
	CW1CL12.5A (CW1PCL12.5A) (CW1HCL12.5A)	12.5	6.5	4.0±0.5	0.8	56	2000	CW1 (CW1P) (CW1H)
	CW1CL15A (CW1PCL15A) (CW1HCL15A)	15.0	5.3	4.5±0.5	0.8	56	2000	CW1 (CW1P) (CW1H)
	CW2CL15A (CW2PCL15A) (CW2HCL15A)	15.0	7.0	4.5±0.5	0.8	84	2000	CW2 (CW2P) (CW2H)
	CW2CL20A (CW2PCL20A) (CW2HCL20A)	20.0	8.0	4.5±0.5	0.8	84	2000	CW2 (CW2P) (CW2H)
	CW3CL20A (CW3PCL20A) (CW3HCL20A)	20.0	8.0	4.0±0.5	0.8	160	1000	CW3 (CW3P) (CW3H)
	CW3CL25A (CW3PCL25A) (CW3HCL25A)	25.0	7.0	4.5±0.5	0.8	160	1000	CW3 (CW3P) (CW3H)
	CW5CL30A	30.0	8.5	4.5±0.5	0.8	524	500	CW5
	CW5CL35A	35.0	5.5	4.5±0.5	0.8	524	500	CW5
	MO1/2CL12.5A (MOX1/2CL12.5A)	12.5	6.5	4.0	0.8	52	2000	MO1/2 (MOX1/2)
	MO1/2CL15A (MOX1/2CL15A)	15.0	5.3	4.0	0.8	52	2000	MO1/2 (MOX1/2)
	MO1CL15A (MOX1CL15A)	15.0	7.0	4.0	0.8	69	2000	MO1 (MOX1)
	MO1CL20A (MOX1CL20A)	20.0	4.8	4.0	0.8	69	2000	MO1 (MOX1)
	MO2CL20A (MOX2CL20A)	20.0	8.0	4.0	0.8	142	1000	MO2 (MOX2)
	MO2CL25A (MOX2CL25A)	25.0	7.0	4.0	0.8	142	1000	MO2 (MOX2)
	MO3CL30A (MOX3CL30A)	30.0	8.5	4.0	0.8	460	500	MO3 (MOX3)
	MO3CL35A (MOX3CL35A)	35.0	5.5	4.0	0.8	460	500	MO3 (MOX3)
	MOS1/2CL10A (MOSX1/2CL10A)	10.0	5.3	4.0	0.6	23	2000	MOS1/2 (MOSX1/2)
	MOS1CL12.5A (MOSX1CL12.5A)	12.5	7.0	4.0	0.8	31	2000	MOS1 (MOSX1)
	MOS1CL15A (MOSX1CL15A)	15.0	6.5	4.0	0.8	31	2000	MOS1 (MOSX1)
	MOS2CL15A (MOSX2CL15A)	15.0	7.0	4.0	0.8	71	2000	MOS2 (MOSX2)
	MOS2CL20A (MOSX2CL20A)	20.0	9.0	4.0	0.8	71	2000	MOS2 (MOSX2)
	MOS3CL20A (MOSX3CL20A)	20.0	8.0	4.0	0.8	146	1000	MOS3 (MOSX3)
	MOS3CL25A (MOSX3CL25A)	25.0	7.0	4.0	0.8	146	1000	MOS3 (MOSX3)
	MOS5CL30A (MOSX5CL30A)	30.0	8.5	4.0	0.8	524	500	MOS5 (MOSX5)
	MOS5CL35A (MOSX5CL35A)	35.0	5.5	4.0	0.8	524	500	MOS5 (MOSX5)
	SPR1/2CL10A (SPRX1/2CL10A)	10.0	5.3	4.0	0.6	23	2000	SPR1/2 (SPRX1/2)
	SPR1CL12.5A (SPRX1CL12.5A)	12.5	6.5	4.0	0.8	54	2000	SPR1 (SPRX1)
	SPR1CL15A (SPRX1CL15A)	15.0	5.3	4.0	0.8	54	2000	SPR1 (SPRX1)
	SPR2CL15A (SPRX2CL15A)	15.0	7.0	4.0	0.8	71	2000	SPR2 (SPRX2)
	SPR2CL20A (SPRX2CL20A)	20.0	9.0	4.0	0.8	71	2000	SPR2 (SPRX2)
	SPR3CL20A (SPRX3CL20A)	20.0	8.0	4.0	0.8	141	1000	SPR3 (SPRX3)
	SPR3CL25A (SPRX3CL25A)	25.0	7.0	4.0	0.8	141	1000	SPR3 (SPRX3)
	SPR5CL30A (SPRX5CL30A)	30.0	8.5	4.0	0.8	456	500	SPR5 (SPRX5)
	SPR5CL35A (SPRX5CL35A)	35.0	5.5	4.0	0.8	456	500	SPR5 (SPRX5)
	RCR50 (+) CL15A	15.0	5.3	4.5	0.7	34	2000	RCR50 (+)
	RCR50ENCL15A	15.0	5.3	4.5	0.7	34	2000	RCR50EN
	RCR60CL15A	15.0	5.3	4.5	0.7	34	2000	RCR60
	RCR75CL15A	15.0	7.0	4.5	0.8	69	2000	RCR75
	RCR100CL20A	20.0	8.0	4.0	0.8	142	1000	RCR100
	RCR100CL25A	25.0	7.0	4.0	0.8	142	1000	RCR100
	RK1/4 □CL10A	10.0	5.3	4.5	0.6	23	1000	RK1/4
	RK1 □CL20A	20.0	8.8	4.5	0.8	146	1000	RK1
	CFP1/4CL10A	10.0	6.5	4.5	0.65	23	1000	CFP1/4
	CFPB1/2CL12.5A	12.5	6.5	4.5	0.65	44	1000	CFPB1/2
RF25CL10A	10.0	5.35	5.0	0.6	23	2000	RF25	
RF50CL12.5A	12.5	6.0	5.2	0.6	29	2000	RF50	
RF50CL15A	15.0	6.0	5.3	0.6	29	2000	RF50	
RF1CL12.5A	12.5	6.5	4.8	0.8	46	2000	RF1	
RF1CL15A	15.0	5.3	4.5	0.8	46	2000	RF1	
RF1CL20A	20.0	5.3	4.5	0.8	46	2000	RF1	
RF2CL20A	20.0	8.0	5.0	0.8	141	1000	RF2	
RF2CL25A	25.0	7.0	4.5	0.8	141	1000	RF2	
 U Forming	MFS1/4 □CU	—	5.5Max.	15.0±1.0	0.45	14	2000	MFS1/4
	CFS1/4CU	—	5.5Max.	15.0±1.0	0.45	12	2000	CFS1/4
 U Forming	MF1/4 □CU	—	9.5Max.	30.0±3.0	0.6	23	2000	MF1/4
	MFP1/4□CU	—	9.5Max.	30.0±3.0	0.6	23	2000	MFP1/4
	RK1/4□CU	—	9.5Max.	30.0±3.0	0.6	23	1000	RK1/4
	RK1/4□CUC-5	—	9.5Max.	5.0±1.0	0.6	23	1000	RK1/4
	CF1/4CUCL	—	10.0Max.	10.0±3.0	0.6	23	1000	CF1/4
	CFS1/2CU	—	9.5Max.	30.0±3.0	0.6	44	1000	CFS1/2
	LT1/4CU	—	9.5Max.	28.0±3.0	0.6	23	2000	LT1/4
 U Forming	MO1/2CU (MOX1/2CU)	—	19.5±3.0	15.0Min.	0.7	49	1000	MO1/2 (MOX1/2)
	MO1CU (MOX1CU)	—	24.0±3.0	15.0Min.	0.8	69	1000	MO1 (MOX1)
	MO2CU (MOX2CU)	—	25.0±3.0	15.0Min.	0.8	71	1000	MO2 (MOX2)
	MOS1CU (MOSX1CU)	—	19.5±3.0	15.0Min.	0.8	23	1000	MOS1 (MOSX1)
	MOS2CU (MOSX2CU)	—	22.0±3.0	15.0Min.	0.8	71	1000	MOS2 (MOSX2)
	MOS3CU (MOSX3CU)	—	25.0±3.0	15.0Min.	0.8	146	1000	MOS3 (MOSX3)
	SPR1CU (SPRX1CU)	—	19.5±3.0	15.0Min.	0.8	54	1000	SPR1 (SPRX1)
	SPR2CU (SPRX2CU)	—	22.0±3.0	15.0Min.	0.8	93	1000	SPR2 (SPRX2)
	SPR3CU (SPRX3CU)	—	25.0±3.0	15.0Min.	0.8	141	1000	SPR3 (SPRX3)

□ : T.C.R.

本样本册中记载的产品规格如有变更，恕不一一奉告。订购以及使用之前，请仔细确认规格表的内容。
 用于车载设备、医疗设备、航空设备以及其它涉及人身安全、或可能引起重大损失的设备上时，请务必先与我司联系。这些产品在这类用途中出现故障或失灵可能导致人身事故或严重损坏。
 Specifications given herein may be changed at any time without prior notice. Please confirm technical specifications before you order and/or use.
 Contact our sales representatives before you use our products for applications including automobiles, medical equipment and aerospace equipment.
 Malfunction or failure of the products in such applications may cause loss of human life or serious damage.

Mar. 2015

包装
Packaging

成形形状 Forming Style	成形型号 Forming Type Name	成形尺寸 Forming Dimension (mm)					重量 Weight g/100pcs	基本单位 Basic Unit (pcs)	直形导线型号 Straight Type Name
		P±1	H ₁	H ₂	e Max.	d			
M Forming 	MFS1/4□CM5F	5.0	—	5.0±1.0	2.0	0.45	14	2000	MFS1/4
	MFS1/4□CM5R	5.0	10.0±1.0	—	2.0	0.45	14	2000	MFS1/4
	MFS1/4□CM5W	5.0	—	15.0±1.0	2.0	0.45	14	2000	MFS1/4
	MFS1/2□CM10R	10.0	10.0±1.0	—	2.0	0.6	23	2000	MFS1/2
	MF1/4□CM10F	10.0	—	5.0±1.0	2.0	0.6	23	2000	MF1/4
	MF1/4□CM12.5R	12.5	10.0±1.0	—	2.0	0.6	23	2000	MF1/4
	MF1/2□CM12.5R	12.5	10.0±1.0	—	2.0	0.6	41	2000	MF1/2
	MF1/2□CM15R	15.0	10.0±1.0	—	2.0	0.6	41	2000	MF1/2
	MFP1/4□CM10F	10.0	—	5.0±1.0	1.7	0.6	24	2000	MFP1/4
	MFP1/4□CM12.5R	12.5	10.0±1.0	—	1.7	0.6	24	2000	MFP1/4
	MFP1/2□CM12.5R	12.5	10.0±1.0	—	2.0	0.6	41	2000	MFP1/2
	MFP1/2□CM15R	15.0	10.0±1.0	—	2.0	0.6	41	2000	MFP1/2
	SNF 2CCM5F	5.0	—	5.0±1.0	1.5	0.45	14	2000	SNF 2C
	SNF 2ECM10F	10.0	—	5.0±1.0	1.7	0.6	24	2000	SNF 2E
	SNF 2ECM12.5R	12.5	10.0±1.0	—	1.7	0.6	24	2000	SNF 2E
	SNF 2HCM12.5K	12.5	7.0±1.0	—	2.0	0.7	41	2000	SNF 2H
	SNF 2HCM15K	15.0	7.0±1.0	—	2.0	0.7	41	2000	SNF 2H
	RCR16CM5F	5.0	—	5.0±1.0	2.0	0.45	14	2000	RCR16
	RCR25CM10F	10.0	—	5.0±1.0	2.0	0.6	23	2000	RCR25
	RCR50 (+) CM15F	15.0	—	5.0±1.0	2.0	0.7	40	2000	RCR50
	RCR50ENCM15F	15.0	—	5.0±1.0	2.0	0.7	40	2000	RCR50+
	RCR60CM15F	15.0	—	5.0±1.0	2.0	0.7	40	2000	RCR60
	RCR100CM20E	20.0	—	4.6±1.0	2.0	0.8	120	1000	RCR100
	RK1/4□CM10F	10.0	—	5.0±1.0	1.7	0.6	21	1000	RK1/4
	RK1/4□CM10R	10.0	—	10.0±1.0	1.7	0.6	21	1000	RK1/4
	RK1/4□CM12.5R	12.5	—	10.0±1.0	1.7	0.6	23	1000	RK1/4
	RK1/2□CM15F	15.0	—	5.0±1.0	2.0	0.6	40	1000	RK1/4
	RK1/2□CM12.5F	12.5	—	5.0±1.0	2.0	0.6	37	1000	RK1/2
	RK1/2□CM15R	15.0	—	10.0±1.0	2.0	0.6	37	1000	RK1/2
	CFS1/4CM5F	5.0	5.9±1.0	5.0±1.0	1.5	0.45	12	2000	CFS1/4
	CF1/4CM10H	10.0	6.0±1.0	4.8±1.0	1.7	0.6	23	1000	CF1/4
	CF1/4CM12.5H	12.5	6.0±1.0	4.8±1.0	1.7	0.6	23	1000	CF1/4
	CFB1/2CM12.5K	12.5	7.0±1.0	5.0±1.0	1.7	0.7	44	1000	CFB1/2
	CFS1/2CM10H	10.0	6.0±1.0	4.8±1.0	1.7	0.6	26	1000	CFS1/2
	CFPS1/4CM5F	5.0	5.9±1.0	5.0±1.0	1.5	0.45	12	2000	CFPS1/4
	CFP1/4CM10H	10.0	6.0±1.0	4.8±1.0	1.7	0.6	23	1000	CFP1/4
	CFPB1/2CM12.5K	12.5	7.0±1.0	5.0±1.0	2.0	0.7	44	1000	CFB1/2
	LT1/6CM5F	5.0	—	5.0±1.0	2.0	0.45	14	2000	LT1/6
	LT1/6CM5R	5.0	10.0±1.0	—	2.0	0.45	14	2000	LT1/6
	LT1/6CM5W	5.0	—	15.0±1.0	2.0	0.45	14	2000	LT1/6
	LT1/4CM10F	10.0	—	5.0±1.0	2.0	0.6	23	2000	LT1/4
	LT1/4CM10R	10.0	10.0±1.0	—	2.0	0.6	23	2000	LT1/4
	LT1/4CM12.5R	12.5	10.0±1.0	—	2.0	0.6	23	2000	LT1/4
	J1/6ZCM7.5H	7.5	—	5.0±1.0	1.5	0.5	5	1000	J1/6Z
	J1/4ZCM10H	10.0	—	5.0±1.0	1.5	0.6	9	1000	J1/4Z
	RF16CM5F	5.0	—	5.0±1.0	2.0	0.45	12	2000	RF16
	RF25CM10X	10.0	16.0±1.0	14.8±1.0	1.5	0.6	23	2000	RF25
	RF50CM12.5E	12.5	—	4.5±1.0	1.5	0.6	29	2000	RF50
	RF1CM15F	15.0	—	5.0±1.0	1.5	0.8	46	2000	RF1
	MO1/2CM15F	15.0	—	5.0±1.0	2.0	0.7	40	2000	MO1/2
	MO1CM15S	15.0	—	11.5±1.5	2.0	0.8	75	2000	MO1
	MO2CM20E	20.0	—	4.6±1.0	2.0	0.8	120	1000	MO2
	MO2CM25C	25.0	—	3.5±1.0	2.0	0.8	120	1000	MO2
	MOX1/2CM15F	15.0	—	5.0±1.0	2.0	0.7	40	2000	MOX1/2
	MOX1CM15S	15.0	—	11.5±1.5	2.0	0.8	75	2000	MOX1
	MOX2CM20E	20.0	—	4.6±1.0	2.0	0.8	120	1000	MOX2
	MOX2CM25C	25.0	—	3.5±1.0	2.0	0.8	120	1000	MOX2
	MOS1/2CM10F	10.0	—	5.0±1.0	2.0	0.6	23	2000	MOS1/2
	MOS1CM12.5D	12.5	—	4.0±1.0	2.0	0.8	31	2000	MOS1
	MOS1CM15F	15.0	—	5.0±1.0	2.0	0.8	31	2000	MOS1
MOS2CM15E	15.0	—	4.5±1.0	2.0	0.8	71	2000	MOS2	
MOS2CM20U	20.0	—	13.5±1.5	2.0	0.8	71	2000	MOS2	
MOS3CM20E	20.0	—	4.6±1.0	2.0	0.8	120	1000	MOS3	
MOSX1/2CM10F	10.0	—	5.0±1.0	2.0	0.6	23	2000	MOSX1/2	
MOSX1CM12.5D	12.5	—	4.0±1.0	2.0	0.8	31	2000	MOSX1	
MOSX1CM15F	15.0	—	5.0±1.0	2.0	0.8	31	2000	MOSX1	
MOSX2CM15E	15.0	—	4.5±1.0	2.0	0.8	71	2000	MOSX2	
MOSX2CM20U	20.0	—	13.5±1.5	2.0	0.8	71	2000	MOSX2	
MOSX3CM20E	20.0	—	4.6±1.0	2.0	0.8	120	1000	MOSX3	
SPR1/2CM10F	10.0	—	5.0±1.0	2.0	0.6	23	2000	SPR1/2	
SPR1CM12.5D	12.5	—	4.0±1.0	2.0	0.8	44	2000	SPR1	
SPR1CM15F	15.0	—	5.0±1.0	2.0	0.8	44	2000	SPR1	
SPR2CM15E	15.0	—	4.5±1.0	2.0	0.8	71	2000	SPR2	
SPR3CM20E	20.0	—	4.6±1.0	2.0	0.8	120	1000	SPR3	
SPRX1/2CM10F	10.0	—	5.0±1.0	2.0	0.6	23	2000	SPRX1/2	
SPRX1CM12.5D	12.5	—	4.0±1.0	2.0	0.8	44	2000	SPRX1	
SPRX1CM15F	15.0	—	5.0±1.0	2.0	0.8	44	2000	SPRX1	
SPRX2CM15E	15.0	—	4.5±1.0	2.0	0.8	71	2000	SPRX2	
SPRX3CM20E	20.0	—	4.6±1.0	2.0	0.8	120	1000	SPRX3	

□ : T.C.R.

本样本手册中记载的产品规格如有变更，恕不一一奉告。订购以及使用之前，请仔细确认规格表的内容。
 用于车载设备、医疗设备、航空设备以及其它涉及人身安全、或可能引起重大损失的设备上时，请务必事先与我司联系。这些产品在这类用途中出现故障或失灵可能导致人身事故或严重损坏。
 Specifications given herein may be changed at any time without prior notice. Please confirm technical specifications before you order and/or use.
 Contact our sales representatives before you use our products for applications including automotives, medical equipment and aerospace equipment.
 Malfunction or failure of the products in such applications may cause loss of human life or serious damage.